

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	F	ILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/803,434	03/18/2004		Robert Wilmer Rodenbeck	3054-74724	5439
23643	7590	12/15/2004	EXAMINER		INER
BARNES &			BROWN, VERNAL U		
11 SOUTH I INDIANAP				ART UNIT	PAPER NUMBER
	0210, 11.			2635	

DATE MAILED: 12/15/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)				
	10/803,434	RODENBECK ET AL.				
Office Action Summary	Examiner	Art Unit				
	Vernal U Brown	2635				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be timed within the statutory minimum of thirty (30) days will apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	ely filed s will be considered timely. the mailing date of this communication. O (35 U.S.C. § 133).				
Status		•				
1)⊠ Responsive to communication(s) filed on 18 M	arch 2004.					
	action is non-final.					
Disposition of Claims						
4) ⊠ Claim(s) 1-26 is/are pending in the application. 4a) Of the above claim(s) is/are withdray 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) 1-26 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/or	vn from consideration.					
Application Papers	·					
9) ☐ The specification is objected to by the Examiner 10) ☑ The drawing(s) filed on 18 March 2004 is/are: a Applicant may not request that any objection to the o Replacement drawing sheet(s) including the correction 11) ☐ The oath or declaration is objected to by the Ex	a) accepted or b) objected to drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 						
Attachment(s)						
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 6/30/04. 	4) Interview Summary (Paper No(s)/Mail Da 5) Notice of Informal Pa 6) Other:	te				

Art Unit: 2635

DETAILED ACTION

The application of Robert Rodenbeck for Wireless Security Control System filed 3/18/04 has been examined. Claims 1-26 are examined.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1, 2, 4, 10-12, 18 and 24-26 are rejected under 35 U.S.C. 102(e) as being anticipated by Kniffin et al. U.S Patent 6072402.

Regarding claims 1 and 18, Kniffin et al. teaches a wireless security control system (figure 1) for use in a facility having a plurality of doors (col. 5 lines 40-44), the wireless security control system comprising a central access control system (18) in which access information is stored (col. 2 lines 44-45), and a plurality of remote access control systems each being adapted to be mounted to a respective one of the doors of the facility to control the locking and unlocking of the respective door (col. 2 lines 25-31), the central access control system wirelessly transmitting access information to the plurality of remote access control systems prior to any users associated with the access information making any attempts to unlock any of the doors (col. 5 lines 42-47), each of

Art Unit: 2635

the remote access control systems being configured to receive wirelessly and store at least some of the access information from the central access control system (col. 5 lines 53-55), each of the remote access control systems being configured to control the locking and unlocking of the respective door using the access information stored therein, each of the plurality of remote access control systems making a decision whether to unlock the respective door in response to a user making an attempt to unlock the door based on the access information stored therein and without having to further communicate with the central access control system (col. 5 lines 53-57).

Regarding claim 2, Kniffin et al. teaches the remote access control systems includes an antenna, an access controller, and a receiver that is electrically coupled to the antenna and that communicates the wireless information received by the antenna to the access controller (figure 1).

Regarding claim 4, Kniffin et al. teaches the remote access control systems is further adapted to transmit wireless information to the central access control system (col. 4 lines 54-56).

Regarding claim 10, Kniffin teaches a remote access control system (figure 1) adapted to be mounted to a door to control the locking and unlocking of the door and adapted to receive wireless information from a central access control system located remotely from the access control system (col. 2 lines 31-40), the remote access control system comprising:

a reader (proximity detector) adapted to read user data presented to reader (col. 3 lines 56-58);

Art Unit: 2635

a remote wireless communicator adapted to receive wireless information from the central access control system, the wireless information being transmitted to the remote wireless communicator where it is stored prior to a user making an attempt to unlock the door (col. 2 lines 44-53);

a remote access controller electrically coupled to the remote wireless communicator and configured to receive the information from the remote wireless communicator, the remote access controller being configured to control the locking and unlocking of the door using the stored wireless information, the remote access controller making a decision from the previously stored wireless information and without requiring additional information from the central access control system about whether to unlock the door in response to the user making the attempt to unlock the door (col. 4 line 52-col. 5 line 2). Kniffin et al. further teaches providing user-updated information to the remote access controller (col. 5 lines 52-55).

Regarding claim 11, Kniffin et al. teaches the remote access control systems further comprises a battery coupled to the respective reader, the respective remote access controller, and the respective remote wireless communicator (col. 4 lines 53-55, figure 1).

Regarding claim 12, Kniffin et al. teaches the user data is stored on tokens (col. 3 lines 50-58), each of the remote access control systems is adapted to store user history information regarding which tokens were granted access (col. 4 lines 52-53), and each of the remote access control systems is configured to transmit the user history information to the central access control system (col. 4 lines 54-56).

Regarding claim 24, Kniffin et al. teaches the central wireless communicator communicates with more than one remote access control system (col. 7 lines 20-25).

Art Unit: 2635

Regarding claims 25-26, Kniffin et al. teaches each of the remote access control systems further includes a reader (28) electrically coupled to the remote access controller and adapted to read user data and each of the remote access control systems periodically transmits the associated user data to the central access controller (col. 4 lines 54-56).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claim 3 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kniffin et al. U.S Patent 6072402 in view of Goldman U.S Patent 5321963.

Regarding claim 3, Kniffin et al. teaches mounting a portion of the remote access control system on both side of the door (col. 5 lines 48-50) but is silent on teaching the remote access control system includes a housing having an inner portion mounted on the inside of the door and an outer portion mounted on the outside of the door. One skilled in the art recognizes that it is conventional practice to have an access control system in which an inner portion of the system is mounted on the inside and an outer portion mounted on the outside in order to allow the access control mechanism to be operated from both side of the door as further evidenced by Goldman (col. 1 lines 59-63).

Art Unit: 2635

It would have been obvious to one of ordinary skill in the art for the remote access control system to include a housing having an inner portion mounted on the inside of the door and an outer portion mounted on the outside of the door in Kniffin et al. as evidenced by Goldman because Kniffin et al. suggests a remote access control system controlling a door and one skilled in the art recognizes that it is conventional practice to have an access control system in which an inner portion of the system is mounted on the inside and an outer portion mounted on the outside in order to allow the access control mechanism to be operated from both side of the door as further evidenced by Goldman.

Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kniffin et al. U.S Patent 6072402 in view of Pilney et al. U.S Patent 5298883.

Regarding claim 5, Kniffin et al. teaches a remote access control system having a transmitter (42) and receiver (14) but is however silent on teaching the remote wireless communicator includes a switch for selectively choosing between receiving and transmitting the wireless information. Pilney et al. in an art related invention in the same field of endeavor of wireless system teaches a wireless communicator with a switch for selectively choosing between receiving and transmitting the wireless information (col. 2 lines 20-25).

It would have been obvious to one of ordinary skill in the art for the communicator transmits wireless information to the central access control system and the remote wireless communicator includes a switch for selectively choosing between receiving and transmitting the wireless receiver in Kniffin et al. as evidenced by Pilney et

Art Unit: 2635

al. because Kniffin et al. suggests a wireless communicator for receiving and transmitting wireless information and Pilney et al. teaches a wireless transceiver with a transmit/receive switch for selectively choosing between receiving and transmitting the wireless information and the remote wireless communicator transmitting information to the central access control system provides information to the central controller concerning the status of the lock.

Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kniffin et al. U.S Patent 6072402 in view of Denison et al. U.S Patent 6359547.

Regarding claim 6, Kniffin et al. teaches providing updated information wirelessly to the remote access control system (col. 5 lines 52-55) but is silent on teaching the remote access control system includes a local communication port electrically coupled to the remote access controllers and adapted to provide wired communication from a portal device. Denison et al. in an art related Electronic Access Control Device invention teaches a remote access control system that includes a local communication port (col. 3 lines 36-39).

It would have been obvious to one of ordinary skill in the art for the remote access control system includes a local communication port electrically coupled to the remote access controllers and adapted to provide wired communication from a portal device in Kniffin et al. as evidenced by Denison et al. because Kniffin et al. suggests transmitting information to the remote access control system and Denison et al. teaches a remote access control system that includes a local communication port for providing updates.

Art Unit: 2635

Claims 8-9 and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kniffin et al. U.S Patent 6072402 in view of Bates et al. U.S Patent 6420961.

Regarding claims 8 and 14, Kniffin et al. teaches RF transmission (col. 2 line 28) but is silent on teaching the wireless remote communicator is adapted to receive spread-spectrum RF information. Bates et al. in an art related Wireless Communication System Interfacing Devices teaches a wireless communicating device receiving spread-spectrum signal (col. 7 lines 24).

It would have been obvious to one of ordinary skill in the art for the wireless remote communicator to receive spread-spectrum RF information in Kniffin et al. because Kniffin et al. suggests a wireless remote communicator and Bates et al. teaches a wireless communicating device receiving spread-spectrum signal and spread spectrum allow the received signal to be distinguish from other signal transmitted at the same frequency in order to create a more secure access system.

Regarding claim 9, Kniffin et al. teaches the remote wireless communicator is adapted to receive and transmit RF information (col. 2 line 28).

Claims 7, 13-17, 19-23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kniffin et al. U.S Patent 6072402 in view of MacLellan et al. U.S Patent 6177861.

Regarding claims 7, 13, and 22 Kniffin et al. teaches providing user-updated information to the remote access controller (col. 5 lines 52-55) but is not explicit in teaching how the update is initiated. MacLellan et al. in an art related communication

Art Unit: 2635

system teaches remote unit transmitting status updates to the central controller (col. 3 lines 45-67). The transmission of the remote unit further initiate a transmission from the central control unit in the form of an acknowledgement (col. 5 lines 44-48).

It would have been obvious to one of ordinary skill in the art for the remote access control system to periodically initiate the transmission of user updates to the remote access unit in Kniffin et al. as evidenced by MacLellan et al. because Kniffin et al. suggests transmitting user updates to the remote access unit and MacLellan et al. teaches the use of the remote unit to initiate communication with a central control unit to ensure that data is transmitted when the remote unit is ready to accept data.

Regarding claims 14 and 17, Kniffin et al. teaches a central access controller (20) and a central wireless communicator (26) connected to the central access controller (figure 1). Kniffin et al. further teaches a RF transmission system that include a paging system or a cellular system for transmitting control signal to the remote access unit (col. 2 lines 47-50) but is silent not explicit in teaching a plurality of central wireless communicators connected to the central controller. MacLellan et al. in an art related security system teaches a plurality of central wireless communicators (103) connected to the central controller (figure 1) in order to limit the number of remote unit communicating with each central wireless communicators for avoiding interference.

It would have been obvious to one of ordinary skill in the art to have a plurality of central wireless communicators connected to the central controller in Kniffin et al. as evidenced by MacLellan et al. because Kniffin et al. teaches a central access controller and a central wireless communicator connected to the central access controller and

Art Unit: 2635

MacLellan et al. teaches a plurality of central wireless communicators connected to the central controller in order to limit the number of remote unit communicating with each central wireless communicators for avoiding interference.

Regarding claim 15, Kniffin et al. teaches the central wireless communicator (26) communicating wirelessly with a remote access system (12) as shown in figure 1.

Regarding claim 16, Kniffin et al. teaches the central wireless communicator communicates with more than one remote access control system (col. 7 lines 20-25).

Regarding claims 19-20, Kniffin et al. teaches a security system in which the central controller (20) is connected to the central access communicator (26) by a wired connection (figure 1) but is silent on teaching the central access controller is electrically coupled to the plurality of central access communicators by the bus. MacLellan et al. in an art related security system teaches central access controller is electrically coupled to the plurality of central access communicators by the bus (figure 1) and the bus is further controlled by network protocol (col. 2 lines 54-64) in order to provide a standard communication interface.

It would have been obvious to one of ordinary skill in the art for the central access controller is electrically coupled to the plurality of central access communicators by the bus in Kniffin et al. as evidenced by MacLellan et al. because Kniffin et al. suggests a security system in which the central controller is connected to the central access communicator by a wired connection and MacLellan et al. teaches central access controller is electrically coupled to the plurality of central access communicators by the

Art Unit: 2635

bus and the bus is further controlled by network protocol in order to provide a standard communication interface.

Regarding claims 21 and 23, Kniffin et al. teaches a central access controller (20) and a central wireless communicator (26) connected to the central access controller (figure 1). Kniffin et al. further teaches a RF transmission system that include a paging system or a cellular system for transmitting control signal to the remote access unit (col. 2 lines 47-50). Kniffin et al. is however silent on teaching the central access controller communicate with central access communicators using RF technology. MacLellan et al. the central access controller communicating wirelessly with the central wireless communicators using RF technology (figure 1, col. 4 lines 2-5) as a low cost wireless communication system.

It would have been obvious to one of ordinary skill in the art for the central access controller communicating wirelessly with the central wireless communicators using RF technology in Kniffin et al. as evidenced by MacLellan et al. because Kniffin et suggests a central access controller and a central wireless communicator connected to the central access controller and MacLellan et al. teaches the central access controller communicating wirelessly with the central wireless communicators using RF technology as a low cost wireless communication means.

Art Unit: 2635

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Vernal U Brown whose telephone number is 571-272-3060. The examiner can normally be reached on 8:30-7:00 Monday-Thursday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Michael Horabik can be reached on 571-272-3068. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Vernal Brown

December 1, 2004

MICHAEL HORABIK SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2600

Michael Horalita